



KEY FEATURES

- INVERTER IGBT
- ADJUSTABLE ARC-FORCE, VRD, ANTI-STICK
- ENERGY SAVING, HIGH EFFICIENCY
- LESS SPATTER, GOOD PERFORMANCE
- STABLE ARC, MOLTEN POOL EASY TO CONTROL



Specifications

Model	ARC-250
Power voltage	AC 230±10%
Frequency	50/60Hz
No-load voltage	60V
Output current	30-200A
Rated output	28V
Duty Cycle	60%
Efficiency	85%
Power factor	0.73
Insulation grade	F
Protection grade	IP21
Weight (power source)	9.2 kg
Dimmension	415 x 150 x 295 mm
Electrode φ (max)	4 mm

Come with accessories

- 3 Meters Earth Clamp with standard cable
- 3 Meters Electrode Holder with standard cable



Optional accessories

- 300 Ampere Orange Welding Cable (100% Copper)
- 8 Meters WP26V-25 Scratch Tig Torch Complete with accessories & Sleeve
- Argon Regulator with flowmeter



Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

Showroom
No. 3 Soon Lee Street, Pioneer
Junction #01-37 Singapore 627606

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

www.danoxwelding.com
sales@danoxwelding.com

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432