



KEY FEATURES

- IGBT MODULE INVERTER TECHNOLOGY
- WITH MMA FUNCTION, 2T/4T
- AVAILABLE FOR WIRE Φ 1.0/1.2/1.6
- DIGITAL DISPLAY FOR CURRENT AND VOLTAGE
- EASILY MOVE WITH GAS SYLINDER BY INTEGRATED TROLLY
- EXCELLENT WELDING PERFORMANCE WITH EXTENDED CABLE FOR WIRE-FEEDER
- ADJUSTABLE INDUCTANCE FOR CONTROLLING ARC TO OPTIMIZE WELD PERFORMANCE
- HIGH WELDING EFFICIENCY



| Specifications | |
|----------------------------|---------------------------|
| Model | MIG-5001 |
| Power Voltage | 415V \pm 15% |
| Open Circuit Voltage | 67V |
| Frequency | 50/60Hz |
| Output current | MIG :50-500 MMA:50-500 |
| Duty Cycle | 60% |
| Efficiency | 85% |
| Power Factor | 0.93 |
| Type of wire feeder | Euro Interface |
| Insulation Grade | F |
| Protection grade | IP21S |
| Weight (Power Source) | 47 |
| Dimension (mm) | 815 x 390 x 625 |
| Output Cable | \geq 50mm ² |
| Applicable plate thickness | \geq 8mm |
| Wire (Max) | 1.0/1.2/1.6 |
| Electrode (Max) | 2.6-6.0 |

| Come with accessories |
|--|
| 3 Meters MIG Torch |
| CO2 Heater Regulator with flowmeter |
| 3 Meters Earth Clamp with standard cable |
| Feeder unit with 10 Meters extension cable |
| Optional accessories |
| 300 Ampere Orange Welding Cable (100% Copper) |
| 3 Meters Electrode Holder with standard cable |
| 8 Meters WP26V-25 Scratch Tig Torch Complete with accessories & Sleeve |
| Argon Regulator with flowmeter |



Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Showroom
No. 3 Soon Lee Street, Pioneer
Junction #01-37 Singapore 627606

www.danoxwelding.com
sales@danoxwelding.com

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432