

KEY FEATURES

- INVERTER IGBT ADJUSTABLE
- ARC FORCE EASY IGNITION
- STABLE ARC
- LOW SPATTER
- ENERGY SAVING
- HIGH EFFICIENCY
- SUITABLE FOR ACIDIC & NORMAL ELECTRODES
- TIG WELDING FUNCTION AVAILABLE



Specification	
Model	DC-500
Power voltage	AC 440±10%
Frequency	50/60Hz
No-load voltage	65V
Output current	40-400A
Rated output (V)	36V
Duty Cycle	60%
Efficiency	85%
Power factor	0.93
Insulation grade	F
Protection grade	IP21
Weight	20
Dimension mm	516*263*466
Electrode φ mm	2.5-6.0

Come with accessories

- 3 Meters Earth Clamp with standard cable
- 3 Meters Electrode Holder with standard cable



Optional accessories

- 300 Ampere Orange Welding Cable (100% Copper)
- 8 Meters WP26V-25 Scratch Tig Torch Complete with accessories & Sleeve
- Argon Regulator with flowmeter



Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Showroom
No. 3 Soon Lee Street, Pioneer
Junction #01-37 Singapore 627606

www.danoxwelding.com
sales@danoxwelding.com

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432