



SIMPLE OPERATION



- + Plug & cut
- + Easily accessible filter regulator Engineered for professionals and metal artists

EX-TRA PERFORMANCE



- + Cutting
- + Precise cuts
- + Easy operation

HIGHEST APPLICATION FLEXIBILITY



- + Plate thicknesses up to 10 mm +
- + Lightweight, exceptionally portable
- + Fixed torch with flexible torch package

BEST COST-EFFECTIVENESS



- + Very low investment
- + Lower running costs



Specifications

MODEL	EXTRAFIRE-30H
Input Amp (A)	10-30
Input Voltage (V)	230V ± 15%
Plasma Gas	Compressed Air
Modes	Cutting
Frequency (Hz)	50/60
Input Capacity (Kva)	4.9
Output Voltage (V)	92
Duty Cycle	35% @ 30A, 100% @ 21A
Dimension (mm)	470 x 156 x 282
Weight (Kg)	10.5
Recommended Cutting (mm)	8
Serverance Cutting (mm)	10
Pierce Cutting (mm)	8
Airflow @ (Lpm/Bar)	120 @ 4.5
Input Pressure (Bar/Psi)	10/145
Protection Level	IP23S
Insulation Class	H/F
Cnc Interface	No
Industry 4.0	No

Come with accessories

Plasma Hand Torch Complete with accessories

3 Meters Earth Clamp with standard cable



Optional accessories

300 Ampere Orange Welding Cable (100% Copper)



Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

www.danoxwelding.com
sales@danoxwelding.com

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432

Showroom
No. 3 Soon Lee Street, Pioneer
Junction #01-37 Singapore 627606