

EXTRAFIRE™ 75SD

DANOX
Just Weld It



SIMPLE OPERATION



- + Intuitive control
- + Protected filter regulator
- + Engineered for professional applications

EX-TRA PERFORMANCE




- + Cutting, gouging, grid mode
- + Exact cuts
- + High duty cycle

HIGHEST APPLICATION FLEXIBILITY




- + Plate thicknesses up to 30 mm +
- + Lightweight, exceptionally portable
- + TCS quick change flexible torch packages
- + Suitable for generator use

BEST COST-EFFECTIVENESS



- + Low investment for high performance
- + Enhanced consumable lifetime
- + Reduced costs of ownership



Specifications

MODEL	EXTRAFIRE-75SD
Input Amp (A)	30-75
Input Voltage (V)	400V ± 15%
Plasma Gas	Compressed Air
Modes	Cutting / Gouging
Frequency (Hz)	50/60
Input Capacity (Kva)	14.2
Output Voltage (V)	170 (Extra-boost 220V)
Duty Cycle	100% @ 75A
Dimension (mm)	560 x 400 265
Weight (Kg)	24
Recommended Cutting (mm)	25
Serverance Cutting (mm)	35
Pierce Cutting (mm)	25
Airflow @ (Lpm/Bar)	270 @ 5.5
Input Pressure (Bar/Psi)	10/145
Protection Level	IP23S
Insulation Class	H/F
Cnc Interface	Yes
Industry 4.0	No

Come with accessories

Plasma Hand Torch Complete with accessories

3 Meters Earth Clamp with standard cable



Optional accessories

300 Ampere Orange Welding Cable (100% Copper)



Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

Showroom
No. 3 Soon Lee Street, Pioneer
Junction #01-37 Singapore 627606

www.danoxwelding.com
sales@danoxwelding.com

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432