



KEY FEATURES

- IGBT MODULE INVERTER TECHNOLOGY
- WITH MMA FUNCTION, 2T/4T
- AVAILABLE FOR WIRE $\Phi 0.8/1.0/1.2$
- DIGITAL DISPLAY FOR CURRENT AND VOLTAGE
- EASILY MOVE WITH GAS SYLINDER BY INTEGRATED TROLLEY
- EXCELLENT WELDING PERFORMANCE WITH EXTENDED CABLE FOR WIRE-FEEDER
- ADJUSTABLE INDUCTANCE FOR CONTROLLING ARC TO OPTIMIZE WELD PERFORMANCE
- HIGH WELDING EFFICIENCY



Specifications

Model	MIG-3501
Power Voltage	415V \pm 15%
Frequency	50/60Hz
Output Current	MIG: 40 - 350A MMA: 40 - 350A
Power Factor	0.93
Efficiency	85%
Wire Feeder	Euro Interface
Max. Wire Feeding Speed	18m/min
Wire Spool	15Kg
Protection Grade	IP21S
Insulation Grade	F
Weight	40
Dimension	932 x 430 x 700
Applicable Plate Thickness	8mm above
Wire Diameter (Max)	0.8 - 1.2
Electrode Diameter (Max)	2.6 - 6.0

Come with accessories

- 3 Meters MIG Torch
- CO2 Heater Regulator with flowmeter
- 3 Meters Earth Clamp with standard cable
- Feeder unit with 8 Meters extension cable



Optional accessories

- 300 Ampere Orange Welding Cable (100% Copper)
- 3 Meters Electrode Holder with standard cable
- 8 Meters WP26V-25 Scratch Tig Torch Complete with accessories & Sleeve
- Argon Regulator with flowmeter

