

MIG-500-4VK



SYNERGY
Control
5+1 Pgms.

4-Roll Feeder

5m
Mains Cable with
32A CEE-Plug

Step switched 30

WK
Integrated
Water Cooling

500A
3x400V

Stepmatic industrial MIG/MAG sets are available as separate feeder versions. Advantage: large covered working range. The power source may remain at its spot, while the light weighted separate feeder is moved to the work zone. Both are linked with an interconnection cable available in 5m or 10m length (optional up to 15m). The feeder is equipped with a fully geared 4-roll wire drive, feed correction control can be adjusted either on feeder or on power source (selectable).



Specifications

Model	MIG-500-4VK
Power Voltage	440V±15%
Frequency	50/60Hz
Steps	30
Open Circuit Voltage	17 - 52V
Duty Cycle	35% @ 470A - 500A 100% @ 300A - 320A
Inductor Steps	2
Welding-wire diameter	0.6 - 1.6
Wire Feeder	4-Roll
Insulation grade	IP21
Weight	160
Dimension	975 x 490 x 925

Come with accessories

- 3 Meters MIG Torch
- CO2 Heater Regulator with flowmeter
- 3 Meters Earth Clamp with standard cable
- Feeder unit with 8 Meters extension cable



Optional accessories

- 300 Ampere Orange Welding Cable (100% Copper)



Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

www.danoxwelding.com
sales@danoxwelding.com
Tel: 6756 2801 WA: 9850 1419

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

www.danoxwelding.com
sales@danoxwelding.com

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432