




Product Features:

- ◆ By adopting advanced power switch control technology, it can greatly improve the reliability of the whole machine.
- ◆ By adopting non-contact arc transfer technology, it has 100% success rate of striking.
- ◆ With 100% duty cycle, it is suitable for heavy industry.
- ◆ With automatic protection function on overheat and abnormal power supply, gas pressure and water pressure.
- ◆ Cutting current creep technology can improve the service life of torch parts.

Applications:

- ◆ Suitable for the industries such as vehicle, petroleum, chemical industry, shipbuilding, power construction, architectural ornament, and other industries.



Specifications	
Model	CUT-100
Input Voltage (V)	AC 400V ± 15%
Frequency (HZ)	50/60
Rated Input Current (A)	22
No-load Voltage (V)	301
Output Current Range (A)	30 - 100
Duty Cycle (%)	35% @ 40°C
Power Factor	0.73
Efficiency (%)	80
Insulation Grade	F
Housing Protection Grade	IP21S
Cutting Thickness (mm)	30
Weight (Kg)	33
Dimension (mm)	550 x 310 x 560

Come with accessories

- Plasma Hand Torch Complete with accessories
- Air filter regulator
- 3 Meters Earth Clamp with standard cable



Optional accessories

- 300 Ampere Orange Welding Cable (100% Copper)



Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

Showroom
No. 3 Soon Lee Street, Pioneer
Junction #01-37 Singapore 627606

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

www.danoxwelding.com
sales@danoxwelding.com

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432