



1. Electric outlet: Used for connection of power cable to supply electric power.
2. Speed adjuster: Turn the knob clockwise, and the machine will travel faster.
3. Clutch: The lever operation will stop driving.
4. Drive wheel: Incline the switch in the direction of the arrow to move the machine in that direction.
5. Drive wheel: Engage the clutch (ON) to transmit driving power, and the machine will begin to travel.
6. Torch side handle: This handle adjusts the lateral position of the torch.
7. Handle: Hold the handle to carry the machine. As well as for positioning.
8. Heat shield: The shield protects the machine from the heating flame.
9. Idle wheel

Specifications

MODEL	HK-12
Input Voltage (V)	C220V ±15%
Cutting Thickness (mm)	6-100
Cutting Speed (mm/min)	150-800
Circle Diameter (mm)	290-540
Cutting Edge Sharp (°)	45
Reduction Gear	Single Cone System
Wheel Distance (mm)	160
Dimensions (mm)	350 × 140 × 175
Weight (Kg)	7.5
1 Torch with body (Kg)	10
2 Torch with body (Kg)	14

Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

Showroom
No. 3 Soon Lee Street, Pioneer
Junction #01-37 Singapore 627606

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

www.danoxwelding.com
sales@danoxwelding.com

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432