



KEY FEATURES

- STABLE MOSFET TECHNOLOGY
- WITH MMA FUNCTION
- 2T/4T, POST FLOW
- EASY ARC IGNITION WITH HF
- STABLE ARC WITHOUT SPATTER AND GOOD SHAPING

Come with 2T/4T function



Specifications	
Model	TIG-250A
Power voltage	1PHASE 230±10%
Frequency	50/60Hz
No-load voltage	56V
Output current	15-200A (TIG) / 10-160 (ARC)
Rated output	18V (TIG) / 26.4V (ARC)
Duty Cycle	60%
Efficiency	85%
Power factor	0.73
Insulation grade	F
Protection grade	IP21
Weight (power source)	7.5 kg
Dimmension	375 x 153 x 290 mm
Tungsten Rod ϕ (max)	3.2 mm
Electrode ϕ (max)	4.0 mm

Come with accessories
3 Meters Earth Clamp with standard cable
8 Meters WP26-25 Tig Torch Complete with accessories & Sleeve
Argon Regulator with flowmeter



Optional accessories
300 Ampere Orange Welding Cable (100% Copper)
3 Meters Electrode Holder with standard cable



Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Showroom
No. 3 Soon Lee Street, Pioneer
Junction #01-37 Singapore 627606

www.danoxwelding.com
sales@danoxwelding.com

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432