



Model	RSB-630B	RSB-1250B
Welding stud range	M1-3mm	M1-5mm
Max output energy	630J	1250J
Charging time	0-3S	
Max welding speed	20PCS / 3mm / Min	20PCS / 5mm / Min
	32PCS / 1mm / Min	32PCS / 2mm / Min
Applied Patent	Functional new type patent: <Capacitor Discharge Stud Welding Machine>	
Power supply	110V~220V / 50Hz~60Hz	
Electric wave variation range tolerance	±10%	
Power supply cable specification	3*1.5mm <sup>2</sup>	
Control cable specification	2*0.5mm <sup>2</sup>	
Working cable max lengthening quantity	10m	
Ground cable max lengthening quantity	5m	
Shell protection grade	IP21	
Appearance size	410mm*245mm*290mm	410mm*245mm*290mm
Host machine weight	16kg	20kg
Standard welding gun	SRQ4	

**Singapore HQ**  
Blk 6 Marsiling Industrial Estate Road 1  
#01-14 Singapore 739275

**Myanmar**  
No. 760A, Pyi Htaung Su, Main Road  
65 Quarters, Industrial Zone (2) South Dagon  
Yangon, Myanmar

**Indonesia- Pt. Inti Bangunan Perkasa**  
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau  
29453

**Showroom**  
No. 3 Soon Lee Street, Pioneer  
Junction #01-37 Singapore 627606

www.danoxwelding.com  
sales@danoxwelding.com

**Retail**  
Blok D, No. 5 Jalan Pembangunan 2, Komplek  
Batama, Batam, Kepulauan Riau- 29432