



MODEL	RST-1600-3	RST-2500-3	RST-3150-3
Welding stud range	Φ6-18mm	Φ8-25mm	Φ10-28mm
Max welding current	1600A	2500A	3150A
Stud welding current regulating range	100-1600A	200-2500A	200-3150A
Manual welding current regulating range	100-630A	200-800A	200-1000A
Welding time regulating range	100-2800ms		
Max welding speed	15pcs / 16mm / min	15pcs / 19mm / min	15pcs / 22mm / min
	20pcs / 8mm / min	20pcs / 10mm / min	20pcs / 13mm / min
Applied Patent	Invention patent<Welding Gun Cooling Device>		
Main circuit	Thyristor Full-Bridge Rectifier		
Control circuit	Microprocessor control		
Prevent Repeat welding	Automatic protection		
Electric power supply	220V~440V / 50~60Hz		
Electric wave variation range tolerance	±10%		
Electric power supply	1*10mm ² +3*16mm ²	1*16mm ² +3*25mm ²	1*16mm ² +3*35mm ²
Control cable specification	4*1mm ²		
Working cable max lengthening quantity	100m		
Ground cable max lengthening quantity	20m		
Shell protection grade	IP23		
Appearance size	950mm*480mm*700mm	1060mm*590mm*740mm	1060mm*590mm*740mm
Host machine weight	205kg	342kg	350kg
One set integrates with multifunction	Stud welding, Manual welding		
Gas shield	Optional		
Standard welding gun	SNQ7	SNQ8/SNQ9	

Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Showroom
No. 3 Soon Lee Street, Pioneer
Junction #01-37 Singapore 627606

www.danoxwelding.com
sales@danoxwelding.com

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432