



MODEL	SSC-800i	SSC-1000i	SSC-2000i
Electric power supply	380V/50HZ		
Power grid variation range tolerance	±10%		
Three phase - four wire power supply cable specification	3×10mm+1×6mm		3×16mm+1×6mm
Welding stud material	Carbon steel, Stainless steel, Aluminium etc.		
Ferrule protection welding range	3-12mm	3-14mm	5-22mm
Short cycle welding range	3-8mm	3-12mm	3-12mm
Gas shield welding range	3-10mm	3-12mm	3-12mm
Max welding current	800A	1000A	2000A
Current regulating range	100-800A	100-1000A	300-2000A
Welding time regulating range	5-1000ms		5-3000ms
Pre-ventilation time regulating range	500-2000ms		
Max welding speed	25pcs/min (M8)	25pcs/min (M12)	8pcs/min (M22)
Control cable specification	4×1mm ²		
Working cable max lengthening quantity	50m		
Ground cable max lengthening quantity	20m		
Cooling mode	Air cooling		
Shell protection grade	IP23		
Appearance size	600mm×320mm×400mm	600mm×320mm×400mm	640mm×320mm×700mm
Host machine weight	35kg	38kg	75kg

Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

Showroom
No. 3 Soon Lee Street, Pioneer
Junction #01-37 Singapore 627606

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

www.danoxwelding.com
sales@danoxwelding.com

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432