



Specifications

Model	TIG-200DV
Power voltage	AC 110/220V ± 20%
Frequency	50/60Hz
No-load voltage	42V
Output current	10-200A
Rated output	14.8V/18V
Duty Cycle	60%
Efficiency	85%
Power factor	0.73
Insulation grade	F
Protection grade	IP21
Weight (power source)	14
Dimension	432 x 204 x 302
Tungsten Rod φ (max)	2.4 mm
Electrode φ (max)	-

Come with accessories

- 3 Meters Earth Clamp with standard cable
- 8 Meters WP26-25 Tig Torch Complete with accessories & Sleeve
- Argon Regulator with flowmeter



Optional accessories

- 300 Ampere Orange Welding Cable (100% Copper)
- 3 Meters Electrode Holder with standard cable



Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

www.danoxwelding.com
sales@danoxwelding.com
Tel: 6756 2801 WA: 9850 1419

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

www.danoxwelding.com
sales@danoxwelding.com

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulauan Riau- 29432