TITANTIG-180

DANOX
Just Weld It

KEY FEATURES

- STABLE MOSFET TECHNOLOGY
- 2T/4T, POST FLOW
- EASY ARC IGNITION WITH HF
- STABLE ARC WITHOUT SPATTER AND GOOD SHAPING

Come with 2T/4T function



Specifications	
Model	TITANTIG-180
Input Voltage	230V± 10%
Frequency	50/60Hz
Input Current	22.6
Output Current	TIG: 10-180A MMA: 10-160A
Power Factor	0.7
No Load Voltage	59V
Efficiency	≥ 85%
Duty Cycle	40% @ 180A 60% @ 147A 100% @ 114A
Protection	IP23
Insulation Class	H
Weight	7KG
Dimension	365 x 135 x 277

Come with accessories
3 Meters Earth Clamp with standard cable
8 Meters WP26-25 Tig Torch Complete with accessories & Sleeve
Argon Regulator with flowmeter

Optional accessories
300 Ampere Orange Welding Cable (100% Copper)

Singapore HQ
Blk 6 Marsiling Industrial Estate Road 1
#01-14 Singapore 739275

www.danoxwelding.com
sales@danoxwelding.com
Tel: 6756 2801 WA: 9850 1419

Myanmar
No. 760A, Pyi Htaung Su, Main Road
65 Quarters, Industrial Zone (2) South Dagon
Yangon, Myanmar

www.danoxwelding.com
sales@danoxwelding.com

Indonesia- Pt. Inti Bangunan Perkasa
No. 15-17 Jalan Pelita 1, Batam, Kepulauan Riau
29453

Retail
Blok D, No. 5 Jalan Pembangunan 2, Komplek
Batama, Batam, Kepulaunan Riau- 29432

Specifications, Facelift & Colors are subjected to change without prior notice